



# BAH1662N

Hydraulic accessories test stand

Banc d'essai d'accessoires hydrauliques



Overhaul test of non rotary accessories

Essais statiques ou dynamiques d'accessoires hydrauliques



## TECHNICAL FEATURES

High pressure system	> Max pressure	5000 psi
	> Max. flow	50 USgpm
	> Max. hydraulic power	160000 USgmp x psi
Low pressure system	> Max pressure	100 psi
	> Max. flow	68 USgpm
Hand pump	>Max pressure	8700 psi
	> Displacement	0.4 cu.in

## OPERATING CONDITIONS

Environment	> Workshop conditions
Fluid	> Skydrol
	> mineral fluid as per MIL-H-5606 (AIR 3520B, NATO H515)
Filtration	> Class 5 according to NAS 1638 or AIR 1635A standard

## CARACTÉRISTIQUES TECHNIQUES

Circuit HP	> Pression max.	350 bar
	> Débit max.	190 l/mn
	> Puiss. hydraulique	4200 (l/mn x bar) max
Circuit BP	> Pression max.	7 bar
	> Débit max.	260 l/mn
Circuit pompe à main	> Pression max.	600 bar
	> Cylindrée	7 cm <sup>3</sup>

## CONDITIONS D'UTILISATION

Environment	> Conditions d'atelier
Fluide	> Skydrol
	> Huile minérale conforme à la norme MIL-H-5606 (AIR 3520B, NATO H515)
Filtration	> Classe 5 selon la norme AIR 1653A ou NAS 1638